

REMARKS

After entry of this amendment, claims 1-2, 5-17, and 33-49 remain pending. In the present Office Action, claims 1-32 were rejected under 35 U.S.C. § 102(e) as being anticipated by Coile et al., U.S. Patent No. 6,061,349 ("Coile"). Applicant respectfully traverses this rejection and requests reconsideration.

Claims 1-2 and 5-17

Applicant respectfully submits that each of claims 1-2 and 5-17 recites a combination of features not taught or suggested in the cited art. For example, claim 1 recites a combination of features including: "the second application sending the communication to the first port; a first application requesting the communication from the first port; translating the first port in the request for the communication from the first application to the second port; and delivering the communication to the first application from the second port".

Coile teaches a "Local Director 200 contains a packet interceptor 204 which intercepts packets containing certain destination IP addresses and port numbers. An address and port number translator 206 replaces the destination IP address and destination port number in the packets with the address and port number of a physical machine 210 which implements the virtual machine that corresponds to the destination IP addresses specified by the client on network communication line 202." (Coile col. 5, lines 28-35). Coile further teaches "Outbound packets from physical machine 210 are intercepted by a packet interceptor 218 and the source IP address and port number of those packets is translated by an address and port number translator 220. Packet interceptor 218 and port number translator 220 use connection database 212 to find correct virtual IP address and port number to replace the IP address and port number of physical machine 210 as the source IP address and port number of the packet. Thus, not only is the connection requested by a client to a virtual machine redirected without the client's knowledge to physical machine 210, but the returned packets from physical machine 210 are altered so that it also appears to the client that the return packets are sent from the virtual machine

which the client attempted to access." (Coile, col. 6, lines 28-42). Thus, Coile teaches a local director 200 that translates a virtual IP address and virtual port number from a client packet to the server's IP address and port number. Server packets include the server IP address and port number, which the local director 200 maps to the virtual IP address and virtual port number for packets sent to the client. The server uses its own IP address and port number, presumably unaware of the virtual IP address and virtual port number. The clients use the virtual IP address and virtual port number, unaware of the server's IP address and port number.

These teachings do not teach or suggest "the second application sending the communication to the first port; a first application requesting the communication from the first port; translating the first port in the request for the communication from the first application to the second port; and delivering the communication to the first application from the second port". For at least the above stated reasons, Applicant submits that claim 1 is patentable over the cited art. Claims 2 and 5-17, being dependent from claim 1, are similarly patentable over the cited art for at least the above stated reasons. Each of claims 2 and 5-17 recite additional combinations of features not taught or suggested in the cited art.

New Claims 33-49

Applicant respectfully submits that each of new claims 33-49 recites a combination of features not taught or suggested in the cited art. For example, claim 33 recites a combination of features including: "receiving the communication on the first port from the second application; receiving a request for the communication from a first application, the request including an indication of the first port; translating the first port in the request for the communication from the first application to the second port; and delivering the communication to the first application from the second port". Claims 34-44 depend from claim 33 and recite additional combinations of features not taught or suggested in the cited art.

As another example, claim 45 recites a combination of features including: "the second application is configured to send the communication to the first port; the first application is configured to request the communication from the first port; the first computer is configured to translate the first port in the request for the communication from the first application to the second port; and the first computer is configured to deliver the communication to the first application from the second port". Claims 46-49 depend from claim 45 and recite additional combinations of features not taught or suggested in the cited art.

Specification Objection

The specification was objected to for not including enough spacing between the lines. A substitute specification is included herewith that includes additional spacing. Furthermore, the substitute specification has been amended to correct a serial number in the priority claim and to correct minor typographical/grammatical errors, as shown in the marked-up copy of the substitute specification. Applicant believes that no new matter has been entered.

CONCLUSION


Applicant submits that the application is in condition for allowance, and an early notice to that effect is requested.

If any extensions of time (under 37 C.F.R. § 1.136) are necessary to prevent the above referenced application(s) from becoming abandoned, Applicant(s) hereby petition for such extensions. If any fees are due, the Commissioner is authorized to charge said fees to Meyertons, Hood, Kivlin, Kowert, & Goetzel, P.C. Deposit Account No. 501505/5760-22600/LJM.

Also enclosed herewith are the following items:

- ☒ Return Receipt Postcard
- ☐ Petition for Extension of Time
- ☐ Request for Approval of Drawing Changes
- ☒ Notice of Change of Address
- ☐ Fee Authorization Form authorizing a deposit account debit in the amount of \$
for fees ().
- ☒ Other: IDS and cited reference, substitute specification (marked up and clean copies).

Respectfully submitted,



Lawrence J. Merkel
Reg. No. 41,191
AGENT FOR APPLICANT(S)

Meyertons, Hood, Kivlin, Kowert, & Goetzel, P.C.
P.O. Box 398
Austin, TX 78767-0398
Phone: (512) 853-8800

Date: 5/10/07

VIRTUAL PORT MULTIPLEXING

REFERENCE TO RELATED APPLICATIONS

The present application claims priority to and incorporates the following applications
5 by reference: DYNAMIC SYMBOLIC LINK RESOLUTION, Prov. No. 60/157,728, filed
on October 5, 1999; SNAPSHOT VIRTUAL TEMPLATING, Prov. No. ~~60/157,728~~,
60/157,729, filed on October 5, 1999; SNAPSHOT RESTORE OF APPLICATION CHAINS
AND APPLICATIONS, Prov. No. 60/157,833, filed on October 5, 1999; VIRTUAL
RESOURCE-ID MAPPING, Prov. No. 60/157,727, filed on October 5, 1999; and VIRTUAL
10 PORT MULTIPLEXING, Prov. No. 60/157,834, filed on October 5, 1999.

FIELD

The present invention relates generally to the multiplexing of ports. More
specifically, the present invention relates to the rerouting of communication to alternative
15 ports allowing a plurality of computers and/or applications to send and receive data directed
at the same port number.

BACKGROUND

Prior art computers communicate or transmit data through communication channels
20 accessed through ports. A port is an endpoint to a logical connection. Communication
between computers is achieved by forwarding data to a particular address, such as an IP
address, on a predefined port number. Each port has a port number and the port number
identifies what type of port each port is. For example, port 80 is used for HTTP traffic. Ports
are utilized in several different protocol networks including TCP/IP and UDP networks.

When a first application running on a first computer transmits data directed to a second application on a second computer, the first application will transmit the data directed at a predefined port to be received by the second computer and application. If the port is unknown, the data cannot be forwarded. Further, if a first application is currently listening on a given port, a second application that listens on the same port will fail because the port is already in use. The port cannot be initialized for listening by the second application if the port is already in use by the first application.

SUMMARY

To achieve the foregoing, and in accordance with the purpose of the present invention, a method and apparatus is disclosed which provides communication between at least two applications. The communication is achieved by accepting a connection from a second application on a first port and allocating a second port to receive the communication from the second application. Once the second port has been allocated the second port translation is recorded. The communication is sent to the first port from the second application and received on the second port. The communication is then delivered to a first application from the second port. In one embodiment the first application requests the communication from the first port and the first port is translated to determine the second port such that the communication is delivered to the first application in the step of delivering the communication to the first application.

In one embodiment, the communication is received on the first port following the step of sending the data to the first port, the first port is translated to determine the second port prior to the step of receiving the communication on the second port, and the step of receiving the communication on the second port includes queuing the communication on the second port from the first port.

In one embodiment, the second application requests to connect with the first port prior to the step of accepting the connection. Once the second port is allocated, the second port is negotiated including negotiating the second port between a first and second virtual port multiplexer. Further, the second application is connected with the second port following the step of allocating the second port. The step of recording the translation including, first, recording the translation of the second port in association with the first application, and second, recording the translation of the second port in association with the second application.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention, together with further advantages thereof, may best be understood by reference to the following description taken in conjunction with the accompanying drawings in which:

FIG. 1A is a high level block diagram illustrating the various components of a computer network used in connection with the present invention;

FIG. 1B is a high level block diagram a computer which, in one embodiment, is utilized to implement the present virtual port multiplexing;

FIG. 2 shows one implementation of one embodiment of the novel virtual port multiplexing (VPM) system which allows communication between a plurality of computers operating at least one application and/or process;

FIG. 3 shows a simplified block diagram of the VPM similar to that shown in FIG. 2, where, in one embodiment, the VPM system routes the connections $c_{1,4}$ through a virtual port;

FIG. 4 depicts a simplified block diagram of the VPM system providing multiplexing or rerouting of a port allowing communication between at least two applications;

FIG. 5 shows a simplified block diagram of VPM and the communication or data transfer between two applications under the non-cooperative multiplexing once the virtual port has been established as shown in FIG. 4;

FIG. 6 shows a simplified block diagram of the VPM system where cooperative communication is achieved between two applications or processes each communicating through a VPM;

FIG. 7 shows a simplified block diagram of one implementation of one embodiment of the data transfer or communication through the VPM system providing cooperative communication similar to that shown in FIG. 6;

FIG. 8 shows a simplified block diagram of one implementation of one embodiment where cooperative multiplexing is provided between a first application and a second application through a single VPM; and

FIG. 9 shows a simplified block diagram of a computer system or network having an AppShot Framework and at least one application configurator.

DETAILED DESCRIPTION

Among other aspects and innovations, the invention provides structure, system, method, method of operation, computer program product, and business model and method for providing multiplexing of a port, for example a TCP/IP port, into multiple virtual ports.

Where a port, in one embodiment, is a bidirectional software construct identifying a data stream. The novel port multiplexing provided by the present invention allows multiple applications and processes, such as multiple socket-based server processes, to utilize the same port number without interfering with the operation and data transfer associated with each application and process. In one embodiment, the present method and apparatus allows a plurality of different computers to direct data communication at the same port number

without interference, while still maintaining accurate communication. In one embodiment, the present method and apparatus transparently redirects communication to alternate ports establishing independent data streams without an application's knowledge.

By allowing the multiplexing of a port into multiple virtual ports, multiple
5 applications and processes, such as socket-based applications and processes, can monitor, accept and transmit data on the same port number, while each application and process functionally receives a unique port to send and receive data. In one embodiment, the virtual port multiplexing allows two separate instances of the same application to operate on the same computer without interference between the two instances, and while avoiding errors or
10 misdirected data during data communication. For example, two separate instances of the same application will direct data to the same port. Thus potential errors are likely to result due to the separate instances attempting to simultaneously send or receive data on the same port. The present invention will prevent this potential conflict by rerouting at least one of the instances by multiplexing the port and transparently rerouting the at least one instance to an
15 alternative port. Further, the present invention allows a plurality of computers to communicate while the plurality of computers attempt to reference the same port without interfering or corrupting the data transferred. In one embodiment, the virtual port multiplexing is accomplished without interaction from the applications or processes, and further, the applications or processes are unaware of the virtual streams. The applications or
20 processes only have knowledge of the original fixed port number.

FIG. 1A illustrates in high level block diagram form the overall structure of the present invention as used in connection with a global computer network 100 such as the Internet. Remote users 102-1 and 102-2 can connect through the computer network 100 to a private network of computers 106 protected by firewall 104. Computer network 106 is a
25 network comprising computers 108-1, 108-2, through 108-n, where n is the total number of

computers in network 106. Computers ~~150~~ 108 are used to run various applications, as well as host web sites for access by remote users 102. The present invention is implemented on computer network 106 in the form of virtual environments 110-1 and 110-2. While only two virtual environments are illustrated, it is to be understood that any number of virtual environments may be utilized in connection with the present invention.

In one embodiment, the method and system of the present invention is implemented in a computer readable medium, such as a computer program ~~118~~ executed on a computer 120 as illustrated in the high level block diagram of FIG. 1B. As shown, computer 120 incorporates a processor 122 utilizing, in one embodiment, a central processing unit (CPU) and supporting integrated circuitry. A memory 124 which is any type or combination of memory including fast semiconductor memory (e.g., RAM, NVRAM or ROM), slower magnetic memory (e.g., hard disk storage), optical memory and any conventional memory known in the art, to facilitate storage of the computer program ~~118~~ and the operating system software. In one embodiment, also included in computer 120 are interface devices including, but not limited to, keyboard 126, pointing device 130, and monitor 132, which allow a user to interact with computer 120. Mass storage devices such as disk drive 134 and CD ROM 136 may also be included in computer 120 to provide storage of information. Computer 120 may communicate with other computers and/or networks via modem 140 and telephone line 142 to allow for remote operation, or to utilize files stored at different locations. Other media may also be used in place of modem 140 and telephone line 142, such as a direct connection, high speed data line or a wireless connection, and the like. In one embodiment, the components described above may be operatively connected by a communications bus 144. In one embodiment, the components may be operatively connected by wireless communication.

FIG. 2 shows one implementation of one embodiment of the novel virtual port multiplexing (VPM) system 148 which allows communication between a plurality of

computers 152a-d operating at least one application and/or process 154a-g. Accurate communication is maintained by the present VPM system 148 even though the data communicated to and from the plurality of applications 154 are directed to the same port number 156, for example port 9000. The communication of the plurality of applications, all directing and receiving communicated ~~data~~data at the same port number is further achieved without interference between the computers 152a-c and applications 154a-g, and without errors in the communicated data. In one embodiment, the VPM system 148 redirects the communication of the computers 152a-d and applications 154a-g to different virtual ports and thus avoids interferences. The embodiment of FIG. 2 shows that computers 152a-d and applications 154a-g attempting to use the same port 156 are being provided functionally independent connections c_{1-4} across that port 156. FIG. 3 shows a simplified block diagram of the VPM ~~150-148~~ similar to that shown in FIG. 2, where, in one embodiment, the VPM system 148 routes the connections c_{1-4} through a virtual port 158. Functionally, the VPM transparently reroutes communication traffic connections c_{1-4} to separate ports 156a-c thus avoiding interference and errors. The VPM system 148 allows a plurality of computers 152a-d and applications 154a-g to logically operate simultaneously when designating the same port without interfering and without losing information or data.

Still referring to FIGS. 2 and 3, the computers 152 are any computer system or network. For example, computer 152a is a computer having a plurality of servers 160a-c providing application processing. Computers 152b-c are individual computers providing a client or client application 162a-b with access to computer 152a and server applications 160a-c. Computer 154d is a computer network having at least two clients 162c-d allowing access to computer 152a and servers 160a-c. In one embodiment, computer 152 is a single network location or address regardless of the number of physical computers represented by the single address, whether operating server applications 160 or client applications 162. In one

embodiment, servers 160a-c are physically independent computer systems within a computer network 152a. In one embodiment, servers 160a-c are server applications, such as software programs, which provide services by listening and responding to network requests on an IP address and a port, such as port 9000. In one embodiment, a port is a pre-assigned port that is known to provide a predefined service. One example of an server application 160 is a Web Server with a database module that provides real estate listings, that listens on a TCP port 80 for HTTP requests. Another example is a service provided over the Internet such as driving directions and detailed maps obtain from a web site, such as Yahoo Maps®. In one embodiment, clients 162a-d are physically independent computer systems within a computer or computer network. In one embodiment, clients 162a-d are client applications, such as software programs, which attempt to communicate with other computers 152 and/or applications 154 at predefined IP addresses through network connections c_{1-4} directed at predefined ports. An example of a client application is a java applet running within a Web browser, or an internet browser itself such as Netscape Browser® or Internet Explorer®.

FIG. 4 depicts a simplified block diagram of the VPM system 148 providing multiplexing or rerouting of a port 156 allowing communication between at least two applications. In the embodiment shown in FIG. 4, the VPM system 148 provides non-cooperative multiplexing in that only one of the two applications attempting to communicate is rerouted to an alternate port to send and receive data. In one embodiment of non-cooperative multiplexing, a first application, for example server application 160 having an associated IP address, such as 192.168.1.1, and an application identifier (AID) a_1 , requests to listen (step 210) on an initial port p_1 , for example port 9000, for communication or requests from a second application. In one embodiment, AID is a computer network wide unique identifier that corresponds with a specific instance of a running application which is defined in any number of ways including defining the AID in reference to a logical task to be

performed by the associated application, by the logical user that is running the associated application and any other way of defining known in the art. The VPM 150 receives the request from server application 160 and begins to listen on initial port p_1 , port 9000, for a connection or request from a second application (step 212). Once a second application, for example a client application 162 having an associated IP address i_1 , such as 192.168.1.70, attempts to connect with server application 160 at IP address 192.168.1.1 (step 214) through port 9000, VPM 150 receives the connection and a ~~connections~~ connection is accepted (step 216). The VPM 150 multiplexes the communication connection by allocating a second or new port to provide the communication path between server application 160 and client application 162 (step 220). A new port p_2 is then returned (step 222), for example port 12760, to VPM 150. The VPM 150 then records the port translation of the new port p_2 by associating at least the new port p_2 with the AID a_1 for the server application 160 and the IP address i_1 of the client application 162 (step 224) to allow mapping between the initial port p_1 , port 9000, and the new port p_2 , port 12760. Once the VPM 150 has allocated and recorded the new port p_2 , data can be transferred between the applications utilizing the virtual port 9000 which is functionally the new port p_2 . In one embodiment, recording the port translation is achieved by adding the new port number along with the associated IP addresses and AIDs in a lookup table.

FIG. 5 shows a simplified block diagram of VPM 150 and the communication or data transfer between two applications under the non-cooperative multiplexing once the virtual port has been established as shown in FIG. 4. Once VPM 150 has multiplexed the port connection to the new port p_2 , the applications can begin communication and data transfer. For example, client application 162 sends data to server application 160 at IP address 192.168.1.1 directed to the initial port p_1 , port 9000 (step 230). The VPM 150 receives the data sent to port 9000 (step 232). The VPM 150 translates the initial port to determine the

new port in which to redirect the data sent from the client application 162 (step 234). In one embodiment, the translation is achieved by relating the new port p_2 with at least the source IP address of the client application 162. In one embodiment, the new port p_2 is further related with the AID of the server application 160, and the initial port p_1 , port 9000. In one

5 embodiment, the VPM 150 utilizes a translation look-up table to determine the new port p_2 based on at least the server AID a_1 and the client application IP address i_1 . Once the VPM 150 determines the new port p_2 , the data is redirected and queued on the new port p_2 (step 236). Once queued, the data is received over the new port p_2 (step 240). Once the server application 160 requests to read data on the initial port p_1 , port 9000 (step 242), the VPM 150

10 translates the initial port p_1 to determine the multiplexed virtual port p_2 , port 12760 (step 244). The data will then be forwarded from the new port p_2 to the server application 160 (step 246). From the server application's view, the data will appear to be received from the initial port p_1 , port 9000. Thus, the server application 160 receives the data from a virtual port 9000.

15 FIG. 6 shows a simplified block diagram of the VPM system 148 where cooperative communication is achieved between two applications or processes each communicating through a VPM 150a-b. As an example, the server application 160, with IP address 192.168.1.1 and AID a_1 , requests to listen (step 260) on an initial port, for example port 9000. A first VPM 150a receives the request and begins to listen on the initial port p_1 (step 262).

20 When client application 162, with IP address 192.168.1.70, requests to connect to server application 160 at IP address 192.168.1.1 on the initial port p_1 (step 264), a second VPM 150b receives the request and connects to server application 160 through the initial port p_1 (step 266). Following the client application request to connect with the initial port p_1 , the connection is accepted (step 270), the first VPM 150a allocates a new port (step 272), and the

25 new port p_2 , for example port 12760, is returned (step 274). The first VPM 150a then listens

on the new port p_2 . The first VPM 150a will signal the second VPM 150b to negotiate or record the new port p_2 such that the client application 162 establishes a new communication connection to the server application 162 at 192.168.1.1 on the new port p_2 , port 12760 (step 280). In one embodiment, negotiation between the first VPM 150a and the second VPM 150b to establish the new communication path through the new port p_2 is achieved if the client server 162 has an AID which matches the AID of the server application. If the AIDs of both applications do not match, the negotiation of the new port p_2 fails. As one example, the first VPM 150a sends a communication or message to the second VPM 150b that contains at least one AID a_1 of the server application 160 listening on the initial port p_1 (i.e., port 9000).

10 The first VPM 150a may also forward the IP address and port of the requesting client application 162, and the new port p_2 (i.e., port 12760). The second VPM 150b receives the negotiation message and the second VPM 150b finds the AID a_1 corresponding to the requesting client IP address and port. If no AID is listed for that client IP address and port, the connection is terminated. If an AID is listed for that client IP address and port number,

15 but does not correspond to any of the AIDs sent by the first VPM 150a, the connection is terminated. If the AID for that client IP address and port number is found and it does match one of the AIDs sent by the first VPM 150a, the second VPM 150b sends an acknowledgment (step 282) to the first VPM 150a.

Still referring to FIG. 6, once the new port p_2 has been negotiated between both VPMs 150a and 150b, the second VPM 150b acknowledges the new port p_2 to the first VPM 150a (step 282), and connects on the new port p_2 (step 284). Once the second VPM 150b connects with the new port p_2 , the connection is accepted (step 286) by the transport protocol layer 164, such as a TCP layer. The first and second VPMs 150a-b register or record the port translation (step 290 and 292, respectively) and the second VPM 150b returns a virtual port

connection or socket connection to the server application at IP address 192.168.1.1 over virtual port 9000 (step 294).

Once the new port p_2 has been negotiated and translated between both the first and second VPMs 150a-b, both the server and client applications are capable of transmitting and receiving data utilizing the virtual port. FIG. 7 shows a simplified block diagram of one implementation of one embodiment of the data transfer or communication through the VPM system providing cooperative communication similar to that shown in FIG. 6. In this embodiment, the client application 162 is transferring data to the server application 160 through the virtual port p_2 . Initially client application 162 attempts to send data to server application at IP address 192.168.1.1 on an initial port p_1 , for example port 9000 (step 310). The second VPM 150b receives the data and translates the initial port p_1 to the new port p_2 (step 312). In one embodiment, the translation by the second VPM 150b includes obtaining or extracting the client application AID a_1 , the client source IP address (192.168.1.70) and client source port address, for example, port 24111 (not shown). The second VPM 150b then determines the rerouted destination, including server destination IP address (192.168.1.1) and server destination port or new port p_2 (for example, port 12760) as negotiated between first and second VPMs 150a-b (see step 280). Once the port translation is completed and the virtual port is returned, the data is sent over the new port p_2 (step 314) and received on the new port p_2 (step 316). Once the server application 160 requests to read the data on the initial port p_1 (step 320), the first VPM 150a translates the initial port p_1 to the new port p_2 (step 322) as negotiated. Once the first VPM 150a translates the initial port p_1 , the data is then forwarded from the virtual port 9000 (new port p_2) to the server application 160 (step 324).

A similar translation is performed when a response is generated by the server application or when data is forwarded from the server application 160 to the client application 162. For example, when the server application 160 forwards the data to the first VPM 150a,

the first VPM 150a extracts the server application AID a_1 , the server application IP address (192.168.1.1) and the server application port number (9000). Using this information, first VPM 150a ~~preforms~~performs a lookup to determine where to reroute the response. For example, the response is rerouted to client application IP address (192.168.1.70) at client source port address (for example, 24111) through virtual port, which is functionally equivalent to the new port p_2 .

In one embodiment, the redirecting or rerouting of the data to the new port p_2 includes rewriting the protocol headers and recalculating a corresponding checksum. When data is transferred between components of a computer network, often the data being transferred is packetized prior to transferring. The packets of data are often formatted with a header, to identify at least the destination, and usually the source of the data. Many packetized formats include additional information such as IP addresses, port numbers, and checksums in the data structure layout of a packet, such as a TCP packet as defined by a TCP protocol. In one embodiment of the present invention, the data is packetized and these packets are rerouted to the virtual ports as described above. Because the packets are rerouted from an initial port (i.e., port p_1) to alternate ports (i.e., new port p_2), the parameters of the header are altered to reflect the actual port providing the packet communication. In one embodiment, because the packets are being communicated through the virtual port, the headers of the packets are rewritten to designate the virtual port as the communication port. Thus, to ensure that the multiplexing of the ports is transparent to the applications communicating, the VPM system 148 alters the virtual port number in the header of each packet back to the initial port number (i.e., port p_1) before delivering the packets to the destination application or process thus making the virtualization transparent to the destination application or process receiving the packets. Changing the port number changes the checksum of the packet, so the VPM 150 further calculates a new checksum and replaces the old checksum in the packet with a new

checksum. Thus allowing the packets of data to be effectively rerouted to and from the virtual ports transparently.

In one embodiment, virtual port multiplexing of the present invention allows for the implementation of a virtual layer in a protocol stack, such as a TCP/IP protocol stack. The virtual layer is implemented by intercepting a request to bind or connect to a specific socket, allocating an anonymous port, registering or storing a mapping between the original fixed port and the new anonymous port, and redirecting the request to the new port. As described above, packets of data are redirected by rewriting the protocol headers and recalculating the corresponding checksums.

In one embodiment, the present VPM system 148 groups applications or processes attempting to access the same port number. For example, if a first application or process is accessing a first port and has been allocated a first virtual stream, and another different application, another instance of the same application or another process attempts to access the same port number, the VPM system 148 will determine if the second application, instance or process has an AID that matches the first application's AID. If the AID is found to be the same as the first application, the different application, instance or process will receive the same virtualized stream. If the different application, instance or process AID does not match that of the first application's AID, a new virtualized stream is created.

In one embodiment, when VPM system 148 attempts to allocate a new virtualized port, a port must be available. In one embodiment, if a port is not available, the allocation of the virtualized port fails. In one embodiment, if there is not an available port when VPM system 148 attempts to allocate a new virtualized port, the request for the port is queued and VPM system 148 waits for a port to become available. In one embodiment, if the port does not become available within a predefined period, the attempt fails and an error signal is returned.

FIG. 8 shows a simplified block diagram of one implementation of one embodiment where cooperative multiplexing is provided between the first application 160 and the second application 162 through a single VPM 150. As such, the single VPM 150 transparently reroutes the communication through the second port p_2 as described above.

5 FIG. 9 shows a simplified block diagram of a computer system or network 410 having an AppShot Framework 412 and at least one application configurator 414 associated with a first application 160. In one embodiment, the present VPM system 148 is included within the AppShot framework 412. In an alternative embodiment, VPM system 148 is a separate, independent system from the AppShot framework 412 and operates in cooperation with the
10 AppShot framework 412. In one embodiment, the AppShot framework 412 is a software layer that processes relevant transactions between the applications and the operating system. Requests for system resources or changes to process states are routed internally and the AppShot framework 412 tracks these events.

 In one embodiment, the application configurator 414 communicates configuration
15 information regarding the associated application to aid in the initialization of the application. The configuration information includes any information relating to the associated application including, but not limited to, the AID of the associated application, and ports to be multiplexed. In an example for non-cooperative multiplexing, the configurator 414 supplies, for a given application pathname, at least the AID of the application. In one embodiment, the
20 configurator 414 further supplies a list of port numbers, such as TCP port numbers, that are to be multiplexed by VPM and a list of source IP address/port number pairs that should correspond be routed to this AID. In an example for cooperative multiplexing, the configurator 414 supplies at least the AID of the application, and in one embodiment configurator 414 further supplies a list of port numbers that are to be multiplexed.

In one embodiment, the application configurator 414 operates without assistance from the application associated with the configurator 414. One example of an application configurator 414 is an application library. In one embodiment, application configurator 414 exists in the server application environment. In one embodiment, the application configurator 414 is implemented as a server process that proxies application information to an operating system as needed.

In one embodiment, the present invention further provides snapshot virtual templating by creating virtual application templates for the purpose of propagating a single application snapshot into multiple, distinct images. Snapshot virtual templates allow multiple application instances to use the same fixed resource identifier by making the resource identifier virtual, privatizing it, and dynamically mapping it to a unique system resource identifier. When a snapshot is cloned from a virtual template, the common or shared data is used exactly as is, whereas the non-sharable data is either copied-on-write, multiplexed, virtualized, or customized-on-duplication. The present invention greatly reduces the required administrative setup per application instance. Snapshot virtual templating works by noting access to modified resources, fixed system IDs/keys and unique process-related identifies and automatically inserting a level of abstraction between these resources and the application. The resources contained in a snapshot virtual template can be dynamically redirected at restore time. Access to memory and storage is managed in a copy-on-write fashion. System resource handles are managed in a virtualize-on-allocate fashion or by a multiplex-on-access mechanism. Process-unique resources are managed in a redirect-on-duplicate fashion. Rules may be defined through an application configurator that allows some degree of control over the creation of non-sharable data.

In one embodiment, the present invention further provides snapshot restoring by saving all process state, memory, and dependencies related to a software application to a

snapshot image. Interprocess communication (IPC) mechanisms such as shared memory and semaphores must be preserved in the snapshot image as well. IPC mechanisms include any resource that is shared between two process or any communication mechanism or channel that allow two processes to communicate or interoperate is a form of IPC. Sockets, shared memory, semaphores and pipes are some examples of IPC mechanisms. Between snapshots, memory deltas are flushed to the snapshot image, so that only the modified-pages need be updated. Software modules that track usage of resources and their corresponding handles are included as part of the snapshot/restore framework of the present invention. At snapshot time, state is saved by querying the operating system kernel, the application snapshot/restore framework components, and the process management subsystem that allows applications to retrieve internal process-specific information not available through existing system calls. At restore time, the reverse sequence of steps for the snapshot procedure is followed and state is restored by making requests to the kernel, the application snapshot/restore framework, and the process management subsystem.

The present invention has been described generally as operating under or in cooperation with a TCP/IP protocol, however, the virtual port multiplexing apparatus and method is capable of providing virtual port multiplexing for communications and data being transferred under substantially any communication protocol. For example, the present VPM system 148 is capable of providing port multiplexing for protocols which supports point-to-point data links.

Having disclosed exemplary embodiments and the best mode, modifications and variations may be made to the disclosed embodiments while remaining within the scope of the present invention as defined by the following claims.

WHAT IS CLAIMED IS:

1. A method of providing communication between at least two applications, comprising the steps of:

accepting a connection from a second application on a first port;

5 allocating a second port to receive the communication from the second application;

recording the translation of the second port;

sending the communication to the first port from the second application;

receiving the communication on the second port; and

delivering the communication to a first application from the second port.

10

2. The method as claimed in claim 1, further comprising the step of:

listening on the first port for the connection from the second application.

3. The method as claimed in claim 1, further comprising the step of:

15 the first application requesting the communication from the first port; and

translating the first port in the request for the communication to determine the second port such that the communication is delivered to the first application in the step of delivering the communication to the first application.

20 4. The method as claimed in claim 1, further comprising the steps of:

receiving the communication on the first port following the step of sending the data to the first port; and

translating the first port to determine the second port prior to the step of receiving the communication on the second port.

25

5. The method as claimed in claim 4, wherein:

the step of receiving the communication on the second port including queuing the communication on the second port from the first port.

5 6. The method as claimed in claim 1, further comprising the steps of:

the second application requesting to connect with the first port prior to the step of accepting the connection.

7. The method as claimed in claim 1, further comprising the steps of:

10 negotiating the second port following the step of allocating the second port;

8. The method as claimed in claim 7, wherein:

the step of negotiating including negotiating the second port between a first and second virtual port multiplexer.

15

9. The method as claimed in claim 1, further comprising the steps of:

connecting the second application with the second port following the step of allocating the second port.

20 10. The method as claimed in claim 9, wherein:

the step of recording the translation including:

a) recording the translation of the second port in association with the first application; and

25 b) recording the translation of the second port in association with the second application.

11. The method as claimed in claim 10, wherein:

the step of recording the translation of the second port in association with the first application including recording the translation in a first virtual port multiplexer.

5

12. The method as claimed in claim 11, wherein:

the step of recording the translation of the second port in association with the second application including recording the translation in a second virtual port multiplexer.

10 13. The method as claimed in claim 10, wherein:

the step of sending the communication to the first port from the second application including directing the communication at a first port number and translating the first port number to a second port number; and

15 sending the communication to the second port utilizing the second port number prior to the step of receiving the communication on the second port.

14. The method as claimed in claim 9, further comprising the step of:

returning to the second application a virtual socket connection to the first port prior to the step of sending the communication to the first port from the second application.

20

15. The method as claimed in claim 1, wherein:

the step of delivering the communication to the first application from the second port including rewriting the communication to appear to the first application as though the communication is delivered from the first port.

25

16. The method as claimed in claim 15, wherein:

the step of rewriting including rewriting a header of the communication to include at least the first port.

5 17. The method as claimed in claim 16, wherein:

the step of rewriting including rewriting the header of the communication to include a revised checksum.

18. A computer system providing a method for multiplexing at least one port, comprising
10 the steps of:

receiving a request to access a first port from a first application;
receiving a connection on the first port from a second application;
allocating a new port; and
returning the connection to the new port.

15

19. The computer system as claimed in claim 18, further comprising the step of:

translating the new port including determining an application identifier (AID) and internet protocol (IP) address.

20 20. The computer system as claimed in claim 19, further comprising the step of:

negotiating the new port prior to the step of translating the new port.

21. The computer system as claimed in claim 20, further comprising the step of:

acknowledging the new port prior to the step of translating of the new port;
25 returning the virtual port connection to the second application;

22. The computer system as claimed in claim 21, further comprising the step of:
the second application requesting connection to the first port prior to the step of
receiving a connection.

5

23. A computer program product for performing virtual port multiplexing of a plurality of
ports to allow communication between at least a first and second computer, the computer
program product including a computer readable medium and a computer program mechanism
stored thereon, the computer program mechanism comprising:

10 a virtual port multiplexing procedure configured to:

- a) accept a connection from a second application on a first port;
- b) allocate a second port to receive the communication from the second
application;
- c) record the translation of the second port;
- 15 d) send the communication to the first port from the second application;
- e) receive the communication on the second port; and
- f) deliver the communication to a first application from the second port.

24. The computer program product as claimed in claim 23, further comprising the step of:
20 listening on the first port for the connection from the second application;
the first application requesting the communication from the first port;
translating the first port in the request for the communication to determine the second
port such that the communication is delivered to the first application in the step of delivering
the communication to the first application;

receiving the communication on the first port following the step of sending the data to the first port; and

translating the first port to determine the second port prior to the step of receiving the communication on the second port.

5

25. The computer program product as claimed in claim 23, further comprising the steps of:

negotiating the second port following the step of allocating the second port including negotiating the second port between a first and second virtual port multiplexer;

10 connecting the second application with the second port following the step of allocating the second port; and

the step of recording the translation including:

a) recording the translation of the second port in association with the first application; and

15 b) recording the translation of the second port in association with the second application.

26. An apparatus for providing communication between at least two computers, the apparatus comprising:

20 a first computer coupled with a first virtual port multiplexer;

at least a first and second port coupled with the first virtual port multiplexer;

a second computer coupled with at least the first port, and the second computer configured to at least direct communication to the first port;

25 the first computer configured to at least receive the communication from the second port; and

the first virtual port multiplexer configured to at least record a translation of the first port in relation to the second port.

27. The apparatus as claimed in claim 26, further comprising:

5 a second virtual port multiplexer coupled with the second computer and with at least the first and second ports; and

the second virtual port multiplexer configured to at least record the translation of the first port to the second port.

10 28. The apparatus as claimed in claim 27, wherein:

the first virtual multiplexer couples with the second virtual multiplexer such that the first and second virtual multiplexers are configured to at least communicate the translation between the first port and the second port.

15 29. The apparatus as claimed in claim 26, wherein:

the first computer further configured to operate a first application;
the second computer further configured to operate a second application; and
the first and second applications being configured to communicate such that the second computer at least directs the communication from the second application and the first
20 computer at least receives the communication for the first application.

30. The apparatus as claimed in claim 26, wherein:

the first multiplexer is configured to rewrite the communication to at least appear to the first computer that the communication is received from the first port.

25

31. The apparatus as claimed in claim 30, wherein:

the first multiplexer having a means for translating at least the first port in relation to the second port.

5 32. The apparatus as claimed in claim 30, wherein:

the first multiplexer having a lookup table to translate the first port in relation to the second port.

ABSTRACT

To achieve the foregoing, and in accordance with the purpose of the present invention, a method and apparatus is disclosed which provides communication between at least two applications. The communication is achieved by accepting a connection from a second application on a first port and allocating a second port to receive the communication from the second application. Once the second port has been allocated the second port translation is recorded. The communication is sent to the first port from the second application and received on the second port. The communication is then delivered to a first application from the second port. In one embodiment the first application requests the communication from the first port and the first port is translated to determine the second port such that the communication is delivered to the first application in the step of delivering the communication to the first application.